

CAP Ac (RBcAPGI-5acD2ND)

MikroTik cAP ac (RBcAPGI-5acD2nD), dual-band (2.4 GHz və 5 GHz) dəstəyi, 2 gigabit port və PoE ilə qidalanma imkanına sahib tavana montaj olunan Wi-Fi access point-dir. Ofis, kafe və ictimai məkanlar üçün ideal şəbəkə həllidir. Kompakt və estetik dizaynı ilə həm texniki, həm də vizual baxımdan üstünlük yaradır.



Model	cAP ac (RBcAPGI-5acD2ND)
Brend	Mikrotik
WIFI	WiFi5
Genişlik	Dual band
PoE	PoE
Tezlik	2.4Ghz/5Ghz
Qoşulma sayı	100+

Specification

Details	
Product code	RBcAPGI-5acD2nD
Architecture	ARM 32bit
CPU	IPQ-4018
CPU core count	4
CPU nominal frequency	488-896 (auto) MHz
Switch chip model	IPQ-4018
Dimensions	Round case: Ø 136 mm, height: 30 mm; Square case: 145 mm x 145 mm x 30 mm
RouterOS license	4
Operating System	RouterOS
Size of RAM	128 MB
Storage size	16 MB
Storage type	FLASH
MTBF	Approximately 100'000 hours at 25C
Tested ambient temperature	-40°C to 50°C
IPsec hardware acceleration	Yes
Details	

Details	
Wireless 2.4 GHz Max data rate	300 Mbit/s
Wireless 2.4 GHz number of chains	2
Wireless 2.4 GHz standards	802.11b/g/n
Antenna gain dBi for 2.4 GHz	2
Wireless 2.4 GHz chip model	IPQ-4018
Wireless 2.4 GHz generation	Wi-Fi 4
Wireless 5 GHz Max data rate	867 Mbit/s
Wireless 5 GHz number of chains	2
Wireless 5 GHz standards	802.11a/n/ac
Antenna gain dBi for 5 GHz	2.5
Wireless 5 GHz chip model	IPQ-4018
Wireless 5 GHz generation	Wi-Fi 5
WiFi speed	AC1200
Details	
10/100/1000 Ethernet ports	2
Details	
Number of DC inputs	1 (PoE-IN)
Max power consumption	24 W
Max power consumption without attachments	12 W
Cooling type	Passive
PoE in	802.3af/at
PoE in input Voltage	17-57 V
Details	
PoE-out ports	Ether2
PoE out	Passive PoE up to 57V
Max out per port output (input 18-30 V)	500 mA
Max out per port output (input 30-57 V)	400 mA
Max total out (A)	500 mA
Details	
Certification	CE, FCC, IC, EAC, ROHS
IP	20
Details	
Mode button	Yes