

# TAPO C410 KiT

## TP-LINK TAPO C410 KiT SOLAR-POWERED (Rechargeable Lithium-ion Battery) SECURITY WI-FI CAMERA

|                     |                |
|---------------------|----------------|
| Model               | TAPO C410 KiT  |
| Brend               | Tp-Link        |
| Meqapixel           | 3 MP           |
| Səs                 | İkitərəfli səs |
| Enerji mənbəyi      | Batareya       |
| Gecə görmə məsafəsi | 10m            |
| Micro SD            | 512Gb          |
| Internet            | Wifi           |



### Specification

| CAMERA               |                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------|
| Image Sensor         | 1/2.8" Progressive Scan CMOS Starlight Sensor                                                               |
| Lens                 | Focal Length: 3.17 mm<br>Aperture: F1.65<br>Field of View: 125° (Diagonal), 111°(Horizontal), 56°(Vertical) |
| Night Vision         | 850 nm IR LED (30 ft / 9.1 m)<br>Full-Color Night Vision                                                    |
| Lighting             | 2× Spotlights                                                                                               |
| Interface & Button   | 1× POWER Button<br>1× RESET Button<br>1× MicroSD Card Slot (Up to 512GB)                                    |
| SOLAR PANEL          |                                                                                                             |
| Connection Capacity  | A solar panel can only connect to one camera.                                                               |
| Output Port          | Type-C                                                                                                      |
| VIDEO & AUDIO        |                                                                                                             |
| Maximum Resolution   | 2K 3MP (2304 × 1296 px)                                                                                     |
| Frame Rate           | 15 fps                                                                                                      |
| Video Compression    | H.264                                                                                                       |
| Live View            | Yes                                                                                                         |
| Image Enhancement    | 3D DNR<br>WDR                                                                                               |
| Audio Input & Output | Built-in Microphone and Speaker                                                                             |

|                             |                                                                                                                                                                                                                                                                                                          |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CAMERA                      |                                                                                                                                                                                                                                                                                                          |
| Audio Communication         | Two-Way Audio with Noise Cancellation                                                                                                                                                                                                                                                                    |
| Siren Volume                | 94 dB (Level measured at 4-inch/10-cm distance)                                                                                                                                                                                                                                                          |
| STORAGE                     |                                                                                                                                                                                                                                                                                                          |
| Local Storage               | MicroSD Card Slot on Camera (Up to 512 GB)                                                                                                                                                                                                                                                               |
| Cloud Storage               | Tapo Care Cloud Storage Services (Subscription required)                                                                                                                                                                                                                                                 |
| DETECTION and NOTIFICATIONS |                                                                                                                                                                                                                                                                                                          |
| Sensor                      | Single Motion Sensor (FOV: 110° horizontal)<br>Single Ambient Light Sensors                                                                                                                                                                                                                              |
| AI Detection                | Motion Detection<br>Person Detection                                                                                                                                                                                                                                                                     |
| Activity Zones              | Yes                                                                                                                                                                                                                                                                                                      |
| Output Notification         | System Notification<br>System Notification with Snapshot (Tapo Care Services)                                                                                                                                                                                                                            |
| NETWORK                     |                                                                                                                                                                                                                                                                                                          |
| Network Connectivity        | Connect via Wi-Fi                                                                                                                                                                                                                                                                                        |
| Wireless Connectivity       | IEEE 802.11b/g/n, 2.4 GHz Wi-Fi                                                                                                                                                                                                                                                                          |
| SECURITY                    |                                                                                                                                                                                                                                                                                                          |
| Security                    | 128-bit AES Encryption with SSL/TLS<br>WPA/WPA2-PSK                                                                                                                                                                                                                                                      |
| POWER                       |                                                                                                                                                                                                                                                                                                          |
| Power Source                | Built-in Rechargeable Lithium-ion Battery<br>Solar Panel: Tapo A201                                                                                                                                                                                                                                      |
| Input Voltage               | Adapter Input: 100-240 V, 50/60 Hz                                                                                                                                                                                                                                                                       |
| Output Voltage              | Adapter Output: 5.0 V, 1.0 A<br>Solar Panel Max Charging Voltage: 5.2 V<br>Solar Panel Max Charging Power: 2.5 W                                                                                                                                                                                         |
| GENERAL                     |                                                                                                                                                                                                                                                                                                          |
| Smart Integration           | Google Assistant, Amazon Alexa                                                                                                                                                                                                                                                                           |
| Weather Resistance          | IP65                                                                                                                                                                                                                                                                                                     |
| System Requirements         | Tapo App: iOS 11.0 or higher, Andriod 5.0 or higher                                                                                                                                                                                                                                                      |
| Mounting Options            | Tabletop<br>Ceiling-Mounted<br>Wall-Mounted                                                                                                                                                                                                                                                              |
| Operating Temperature       | -20ℳ~45ℳ                                                                                                                                                                                                                                                                                                 |
| Storage Temperature         | -20ℳ~60ℳ                                                                                                                                                                                                                                                                                                 |
| Operating Humidity          | 10%~90% RH, Non-condensing                                                                                                                                                                                                                                                                               |
| Storage Humidity            | 5%~90% RH, Non-condensing                                                                                                                                                                                                                                                                                |
| Charging Temperature        | 0-45ℳ                                                                                                                                                                                                                                                                                                    |
| Dimensions ( W x D x H )    | Camera Dimensions: D60mm x 89mm<br>Solar Panel Dimensions: 173.42 x 120.42 x 15.7 mm (6.83 x 4.74 x 0.62 in)                                                                                                                                                                                             |
| Package Content             | Tapo C410 Camera x1<br>Tapo A201 Solar Panel x1<br>Tapo A201 Solar Panel Bracket x1<br>USB Adapter Cable x1<br>Base Cover x1<br>Extension Wire x1<br>Mounting Screws x6<br>Mounting Anchors x6<br>Waterproof Seals x2<br>Screw Caps x2<br>Cable Zip Tie x1<br>Mounting Templates x2<br>Quick Start Guide |
| Certifications              | CE, FCC, DOE, CEC, RCM, KC, NCC, BSMI, NTRA, IP65                                                                                                                                                                                                                                                        |